



Receptacle Key

- DUPLEX RECEPTACLE
- ⊕ 400V COVER DUPLEX RECEPTACLE (NOT CALLED NOTED)
- ⊕ 250V COVER DUPLEX RECEPTACLE (NOT CALLED NOTED)
- ⊕ 20 AMP
- ⊕ 30 AMP
- ⊕ 40 AMP
- ⊕ GROUND-FULT CIRCUIT INTERRUPTER DUPLEX RECEPTACLE
- ⊕ GROUND-FULT CIRCUIT INTERRUPTER DUPLEX RECEPTACLE (SEA-THERMOPRO)
- ⊕ GROUND-FULT CIRCUIT INTERRUPTER DUPLEX RECEPTACLE (NATIVE COUNTRY)
- ⊕ UNMATCHED DUPLEX OUTLET
- ⊕ SPECIAL PURPOSE OUTLET
- ⊕ DUPLEX FLOOR RECEPTACLE
- ⊕ DUPLEX CEILING RECEPTACLE
- ⊕ GND RECEPTACLE
- ⊕ 250 VOLT OUTLET
- ⊕ PULLSTATION SWITCH
- ⊕ TELEPHONE OUTLET
- ⊕ TELEVISION OUTLET
- ⊕ COMMUNICATIONS OUTLET (VOICE, DATA, AUDIO + VIDEO)

Light Control Key

- ⊕ SINGLE POLE SWITCH
- ⊕ 3-WAY SWITCH
- ⊕ 4-WAY SWITCH
- ⊕ 3-WAY SWITCH WITH PULLSTATION DETECTOR
- ⊕ 3-WAY SWITCH WITH PULLSTATION DETECTOR FOR CONTROL
- ⊕ PULLSTATION SWITCH
- ⊕ REMOTE PULLSTATION COOPERATION SWITCH

GENERAL NOTES:

1. VERIFY RECEPTACLE STYLE AND THERM COLOR WHEN AVAILABLE BEFORE ORDERING.
2. ALL NOTED FINISHING HEIGHTS ARE TO CENTER OF OUTLET.
3. STANDARD HEIGHT FOR LIGHT FIXTURES IS 4'-0" AFF TO CENTER OF SWITCH BOX.
4. INTERFERE WITH ALL DOORS.
5. PROVIDE 4" CEMD OPENING @ 3'0" FROM

Lower Level Plan
SCALE 1/4"=1'-0"